

# Smart Dongle-4G



## Smart

2G, 3G, 4G communication <sup>1</sup>  
Support 3rd-party monitoring system <sup>2</sup>



## Simple

Plug & Play  
Support max. 10 devices



## Reliable

IP65  
Support auto reconnection

| Technical Specification | SDongleA-03-EU |
|-------------------------|----------------|
|-------------------------|----------------|

| General Data                |   |
|-----------------------------|---|
| Max. Devices Supported      | 10                                      |
| Max. Inverters Supported    | 10 <sup>3</sup>                         |
| Connection interface        | USB                                     |
| Installation                | Plug-and-play                           |
| Indicator                   | LED Indicator                           |
| Dimensions (W * H * D)      | 130 x 48 x 33 mm (5.1 x 1.9 x 1.3 inch) |
| Weight                      | 90 g (0.2 lb.)                          |
| Degree of protection        | IP65                                    |
| Power consumption (typical) | 3.5 W                                   |

| Wireless Parameter                |  |
|-----------------------------------|--|
| Sim card type                     | mini-sim (15 mm*25 mm)   |
| Supported standards & frequencies | 4G: FDD-LTE / TDD-LTE<br>3G: WCDMA / HSDPA / HSUPA / HSPA+<br>2G: GSM / GPRS / EDGE <sup>4</sup> |

| Environment                 |                                     |
|-----------------------------|-------------------------------------|
| Operating temperature range | -30 °C to +65 °C (-22 °F to 149 °F) |
| Relative humidity range     | 5 - 95% RH                          |
| Storage temperature range   | -40 °C to +70 °C (-40 °F to 158 °F) |
| Max. operating altitude     | 4,000 m (13,123 ft.)                |

| Standard Compliance (more available upon request) |                                     |
|---|-------------------------------------|
| Certificate                                       | CE, Type Approval for Thailand, MIC |

| Inverter Compatibility |  |
|------------------------|--|
| Inverter model         | SUN2000-2/3/3.68/4/4.6/5/6KTL-L1<br>SUN2000-3/4/5/6/8/10KTL-M0/M1<br>SUN2000-12/15/17/20KTL-M0/M2<br>SUN2000-30/36/40KTL-M3<br>SUN2000-60KTL-M0<br>SUN2000-100KTL-M1 |

1. To ensure stable data transmission, Huawei suggests 4G dongle to be installed in areas with stable mobile signal (2G signal ≥ 4 bars, 3G/4G signal ≥ 3 bars).  
2. 3rd-party management system shall match the communication protocol with Huawei Smart Dongle.  
3. Support 3 inverters only when there is LUNA2000 battery in the system.  
4. For recommended carriers list and details on supported frequencies, please contact local distributors.